



## Fast Recovery Rectifier

### Features

- Fast switching speed for high efficiency
- Low reverse leakage
- High forward surge current capacity
- High temperature soldering guaranteed:  
260°C/10 seconds, 0.375" (9.5mm) lead length
- RoHS and REACH Compliance

### Mechanical Data

<b>Case:</b>	Transfer molded plastic
<b>Polarity</b>	Color band denots cathode end
<b>Lead:</b>	Plated axial lead, solderable per MIL-STD-202E method 208C
<b>Mounting position:</b>	Any
<b>Weight:</b>	0.012 ounce, 0.33 gram

### Maximum Ratings ( $T_{Ambient}=25^{\circ}C$ unless noted otherwise)







Symbol	Description	FR101	FR102	FR103	FR104	FR105	FR106	FR107	Unit	Conditions
<b>VRRM</b>	Max Recurrent Peak Reverse Voltage	50	100	200	400	600	800	1000	V	
<b>VRMS</b>	Max RMS Voltage	35	70	140	280	420	560	700	V	
<b>VDC</b>	Max DC Blocking Voltage	50	100	200	400	600	800	1000	V	
<b>I(AV)</b>	Max Average Forward Rectified Current	1.0							A	TC=75°C (Note 2)
<b>IFSM</b>	Peak Forward Surge Current	30							A	JEDEC method
<b>TJ,TSTG</b>	Operating and Storage Temperature Range	-65 to +150, -65 to +150							°C	
<b>Rθ-JA</b>	Typical Thermal Resistance	50							°C/W	Note 2

### Electrical Characteristics ( $T_{Ambient}=25^{\circ}C$ unless noted otherwise)


Symbol	Description	FR101	FR102	FR103	FR104	FR105	FR106	FR107	Unit	Conditions
<b>VF</b>	Max Instantaneous Forward Voltage	1.3							V	Drop per Bridge element 1.0A
<b>IR</b>	Max DC Reverse Current at Rated DC Blocking Voltage	5.0							μA	TA=25°C
		100							mA	TA=100°C
<b>TRR</b>	Maximum reverse recovery time	150		250			500		nS	Note 1
<b>CJ</b>	Typical Junction Capacitance	15							pF	Measured at 1.0MHz / 4.0V

#### Note:

1. Reverse recovery test conditions:  $I_F=0.5A$ ,  $I_R=1.0A$ ,  $I_{RR}=0.25A$
2. Thermal resistance from junction to ambient with 0.375" (9.5mm) lead length, PCB mounted

**FR101 ~ FR107**
**RATINGS AND CHARACTERISTIC CURVES FR101 THRU FR107**


Dimensions in inches (mm)



Contact us:

**US HEADQUARTERS**

MEI SEMI INC.

2902 Corvin Drive, Santa Clara, CA95051, USA

Tel: 1-408-733-0808 Fax: 1-408-733-2828