




# MB12S thru MB110S

Surface Mount Schottky Bridge Rectifier

Reverse Voltage 20 to 100 Volts Forward Current 1.0 Ampere


## Features

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- High surge overload rating:30A peak
- Saves space on printed circuit boards
- High temperature soldering guaranteed:260 /10 seconds



## Mechanical Data

- Case:Molded plastic body over passivated junctions
- Terminals: plated leads solderable per MIL-STD-750, Method 2026
- Mounting Position:Any
- Weight:0.078 oz.,0.22g



## Maximum Ratings & Electrical Characteristics

( $T_A=25$  unless otherwise noted)

Parameter	Symbol	MB12S	MB14S	MB16S	MB18S	MB110S	Unit
Maximum repetitive peak reverse voltage	$V_{RRM}$	20	40	60	80	100	V
Maximum RMS voltage	$V_{RMS}$	14	28	42	56	70	V
Maximum DC blocking voltage	$V_{DC}$	20	40	60	80	100	V
Maximum Average forward output current	$I_{F(AV)}$	1.0					A
Peak forward surge current 8.3 MS single HALF sine-wave superimposed on rated load (JEDEC Method)	$I_{FSM}$	30					A
Maximum instantaneous forward voltage at 1.0A	VF	0.50		0.70		0.85	V
Maximum DC reverse current at $T_A=25$ rated DC blocking voltage per leg $T_A=100$	IR	0.5					mA
Typical thermal resistance per leg(Note1)	$R_{\theta JA}$	88					/W
	$R_{\theta JL}$	28					
Operation junction temperzture range	$T_J$	-55 to +125					
Storage temperature range	$T_{STG}$	-55 to +150					

**Notes:** 1. Thermal resistance form junction to ambient and from junction to lead P.C.B. mounted on 0.2×0.2"(5.0×5.0mm) copper pad areas.



# MB12S thru MB110S

Surface Mount Schottky Bridge Rectifier

Reverse Voltage 20 to 100 Volts Forward Current 1.0 Ampere

## Ratings and Characteristics Curves

(TA = 25 unless otherwise noted)

Fig.1 Forward Current Derating Curve




Fig.2 Maximum Non-Repetitive Peak Forward Surge Current




Fig.3 Typical Instantaneous Forward Characteristics




Fig.4 Typical Junction Capacitance

